

# MOWERS

WALK BEHIND

# J SERIES

JS25 | JS35 | JS45



"Highest in Customer Satisfaction  
with Walk-Behind Lawn Mowers"\*

# John Deere Walk-Behind Mowers

The walk-behinds that match you stride for stride

- JS25, JS35, and JS45 mowers all feature the unique MowMentum™ Drive System. By just pivoting the handle forward, you can mow at your preferred pace.
- All mowers are powered by Briggs & Stratton engines, which feature a “Fresh Start” cap that automatically drips fuel stabilizer to help prevent stale gas.
- Rugged 21” steel decks include 3-in-1 blades.
- Baggers, mulch plugs and side discharge chutes are standard equipment.
- The JS25 and JS35 offer a rear discharge design; a convenient single lever height of cut adjuster; and Ready Start™, which lets you start with no choking or priming.
- Upgrade to a JS35 for electric start, or to a JS45 which features caster wheels for optimum versatility, and the ability to lock both wheels for improved sidehill mowing.

## Behind you all season long: your John Deere dealer

When you buy a John Deere, you’re getting more than just a machine: you’re getting the knowledge and expertise that only comes from a John Deere dealer. Ask about the variety of service plans available or visit [www.readytomow.com](http://www.readytomow.com) to find out how you can get “Service Delivered” without ever leaving your home.

| SPECIFICATIONS                             | JS25  | JS35  | JS45  |
|--|---|---|---|
| <b>Engine:</b>                             | Briggs and Stratton 675 Series  | Briggs and Stratton 675 Series  | Briggs and Stratton 875 Series  |
| Gross Torque Power**                       | 6.75  | 6.75  | 8.75 OHV  |
| Displacement                               | 190cc   | 190cc   | 190cc   |
| Valves                                     | Side  | Side  | Overhead  |
| Starting                                   | Pull Cord   | Electric Start with pull cord backup                                      | Pull Cord   |
| Choke / Primer                             | Ready Start - No choking or priming                                       | Ready Start - No choking or priming                                       | Primer  |
| Lubrication                                | Splash  | Splash  | Splash  |
| <b>Deck</b>                                | 21” 14 gauge steel  | 21” 14 gauge steel  | 21” 14 gauge steel  |
| Blades                                     | 3-in-1 for use in all applications (mulching, side discharge and bagging) | 3-in-1 for use in all applications (mulching, side discharge and bagging) | 3-in-1 for use in all applications (mulching, side discharge and bagging) |
| Single lever height of cut                 | Yes   | Yes   | No  |
| Height of Cut                              | 9 settings from 1.2” to 4.2”  | 9 settings from 1.2” to 4.2”  | 7 settings from 1.2” to 4.2”  |
| Discharge                                  | Rear  | Rear  | Side  |
| <b>Drive System</b>                        | MowMentum Drive System™   | MowMentum Drive System™   | MowMentum Drive System™   |
| <b>Transmission</b>                        | Variable drive transmission; rear wheel                                   | Variable drive transmission; rear wheel                                   | Variable drive transmission; rear wheel                                   |
| Variable Speed                             | 0-4 mph   | 0-4 mph   | 0-4 mph   |
| <b>Adjustable Handle</b>                   | Standard 3 position   | Standard 3 position   | Standard 3 position   |
| <b>Front Wheels</b>                        | Stationary 8 inch   | Stationary 8 inch   | Caster 8 inch   |
| <b>Rear Wheels</b>                         | 9 inch  | 9 inch  | 9 inch  |
| <b>Bag; Side Discharge and Mulch Ready</b> | Standard  | Standard  | Standard  |
| <b>Bagger Capacity 2.5 bushel</b>          | Standard  | Standard  | Standard  |
| <b>Total Weight</b>                        | 96 lbs  | 105 lbs   | 98 lbs  |



MowMentum Drive™ allows the customer to choose the speed to follow the mower by pivoting the drive handle.



Single lever height adjuster makes it convenient to change the height of cut in nine settings from 1.2” to 4.2”.

\*\* Gross Torque Power: a direct way to measure the turning force an engine can produce.

\*John Deere received the highest numerical score among walk-behind lawn mower manufacturers in the proprietary J.D. Power and Associates 2008 Walk-Behind Lawn Mower Study™. Study based on 2,223 consumer responses, measuring 13 manufacturers and measures opinions of consumers who purchased a walk-behind lawn mower between June 2007 and June 2008. Proprietary study results are based on experiences and perceptions of consumers surveyed in June-July 2008. Your experiences may vary. Visit [jdpower.com](http://jdpower.com).

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of products described in this literature without notice. John Deere's green and yellow color scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company.

