



Compact Utility Tractors

3D, 3R, 4M & 4R Series / 40-66HP



Compact Utility Tractors

3D, 3R, 4M & 4R Series / 40-66HP

	3043D	3046R	4052M HD	4066M HD
ENGINE TYPE	Yanmar Liq-Cooled Diesel	Yanmar Liq-Cooled Diesel	Yanmar Liq-Cooled Diesel	Yanmar Liq-Cooled Diesel
ENGINE HP / PTO HP	*41.6HP/36.3HP	*44.7HP/33.9HP	*51.5HP/40.9HP	*65.9HP/51.9HP
FUEL CAPACITY	9.7 U.S. gal.	10.0 U.S. gal.	15.0 U.S. gal.	15.0 U.S. gal.
HYDRAULIC CAPACITY	10.3 g/m	15.3 g/m	17.4 g/m	17.4 g/m
DRIVE TRAIN	4WD 8F-8R Shuttle	4WD 3-Range eHydro / 4WD 12F-12R Reverser	4WD 3-Range eHydro	4WD 3-Range eHydro
BRAKES	Wet Disk	Multi-Plate Wet Disk	Multi-Plate Wet Disk	Multi-Plate Wet Disk
FRONT/REAR TIRES R4	25x8.5-14/15-19.5	27x8.5-15/43x16-20	31.5x13-16.5/16.9-24	31.5x13-16.5/16.9-24
3-POINT LIFT CAPACITY	2,081 lb (24" Behind)	2,194 lb (24" Behind)	2,500 lb (24" Behind)	2,500 lb (24" Behind)
3-POINT LIFT TYPE	Category 1	Category 1	Category 1 & 2	Category 1 & 2
PTO TYPE	Mechanical	Independent	Independent	Independent
APPROX SHIP WEIGHT	2,840 lb	2,983 lb / 3,570 lb†	4,255 lb	4,290 lb
LENGTH/WIDTH/HEIGHT	115.7 in./58.0 in./92.1 in.	123.8 in./59.7 in./92.8 in.	134.7 in./71.3 in./95.5 in.	134.7 in./71.3 in./95.5 in.
WARRANTY	**10-Year/1,000-Hour	**10-Year/1,000-Hour	**10-Year/1,000-Hour	**10-Year/1,000-Hour
FRONT LOADER	300E Optional	300R / 320R Optional	440R‡	440R‡
LDR LIFT HEIGHT/CAP	84.0 in./1,186 lb	Up to 102.0 in./1,598 lb	110.0 in./2,539 lb	110.0 in./2,539 lb
BACKHOE	N/A	375A / 385A Optional	N/A	N/A

	4044M/R	4052M/R	4066M/R
ENGINE TYPE	Yanmar Liq-Cooled Diesel	Yanmar Liq-Cooled Diesel	Yanmar Liq-Cooled Diesel
ENGINE HP / PTO HP	*43.1HP/32.3HP	*51.5HP/39.0HP	*65.9HP/51.9HP
FUEL CAPACITY	15.0 U.S. gal.	15.0 U.S. gal.	15.0 U.S. gal.
HYDRAULIC CAPACITY	17.4 g/m	17.4 g/m	17.4 g/m
DRIVE TRAIN	4WD 3-Range Hydro / 4WD 12F-12R Reverser	4WD 3-Range Hydro / 4WD 12F-12R Reverser	4WD 3-Range Hydro / 4WD 12F-12R Reverser
BRAKES	Multi-Plate Wet Disk	Multi-Plate Wet Disk	Multi-Plate Wet Disk
FRONT/REAR TIRES R4	10-16.5/16.9Lx24	10-16.5/16.9Lx24	10-16.5/16.9Lx24
3-POINT LIFT CAPACITY	2,500 lb (24" Behind)	2,500 lb (24" Behind)	2,500 lb (24" Behind)
3-POINT LIFT TYPE	Category 1	Category 1	Category 1
PTO TYPE	Independent	Independent	Independent
APPROX SHIP WEIGHT	3,759 lb / 4,675 lb†	3,770 lb / 4,675 lb†	3,770 lb / 4,675 lb†
LENGTH/WIDTH/HEIGHT	128.2 in./72.0 in./96.1 in.	128.2 in./72.0 in./96.1 in.	128.2 in./72.0 in./96.1 in.
WARRANTY	**10-Year/1,000-Hour	**10-Year/1,000-Hour	**10-Year/1,000-Hour
FRONT LOADER	400E / 440R‡ Optional	400E / 440R‡ Optional	400E / 440R‡ Optional
LDR LIFT HEIGHT/CAP	Up to 112.1 in./2,539 lb	Up to 112.1 in./2,539 lb	Up to 112.1 in./2,539 lb
BACKHOE	485A Optional	485A Optional	485A Optional

*Engine HP is provided by the engine manufacturer to be used for comparison purposes only. Actual operating HP will be less. Refer to the engine manufacturer's website for additional information.

**Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com for details.

†When two weights are shown, the heavier weight denotes a factory-installed cab option. ‡440R loader only available on 4R series tractors.



JAMES RIVER
EQUIPMENT

©James River Equipment (1/2021)

For a full list of specifications, available inventory,
buy online options, online credit applications & more,
visit us at www.JamesRiverEquipment.com



JAMES RIVER
EQUIPMENT

3D Series (24.4-41.6HP)

- Final Tier 4 compliant liquid-cooled 3-cylinder diesel engines
- 4WD, synchromesh shuttle two-speed gear drive transmission with 8F-8R gears, column-mounted forward/reverse lever, power steering, and differential lock all come standard
- Open station ROPS with flat operator platform
- Optional iMatch™ Quick Hitch, Quik Knect™ and telescoping draft links make attaching implements fast & easy



3R Series (32.2-45.3HP)

- Final Tier 4-compliant liquid-cooled 3-cylinder diesel engines
- 4WD, three-speed hydrostatic transmission or 12F-12R reverser transmission, power steering, tilt-steering and differential lock all come standard
- Open station ROPS or optional cab with heat & A/C
- Optional iMatch™ Quick Hitch, Quik Knect™ and telescoping draft links make attaching implements fast & easy



4R Series (43.1-65.9HP)

- Final Tier 4-compliant liquid-cooled 3-cylinder diesel engines
- 4WD, three-speed hydrostatic transmission or 12F-12R reverser transmission, power steering, tilt-steering and differential lock all come standard
- Open station ROPS or optional cab with heat & A/C
- Optional iMatch™ Quick Hitch, Quik Knect™ and telescoping draft links make attaching implements fast & easy



Key features (varies by model):



You may not need 4WD every day, but some days nothing else will do.



Sloped hood design gives you the visibility you need for front loader work.



We're green through-and-through, including our hoods. Tough, rust-proof design.



Change or remove a front loader attachment *without* tools in seconds.



Remove and park your front loader in minutes, safely and without tools.



Access your engine easily with hoods that stay open without a prop rod.



Category 1 iMatch™ Quick Hitch, starting at just \$389.



Extra rear and front work lights for working late, starting at just \$99.



Quik Knect™ PTO receivers for easy PTO connections, starting at just \$199.



Skid steer attachment carrier, starting at just \$699.



Canopy kits to keep you cool and in the shade, starting at just \$499.

Most popular attachments (varies by model):

**Ask about our
Extended Warranty
Protection Plans,
starting at just
\$599!**